



# WZY-A7808LC/TA/TB

## 全自动上料8轴包胶绕线机

Automatic Loading 8 Spindle Taping and Winding Machine



### Features

#### 产品特点

- ✓ 机器关键零部件全部采用日本、德国、台湾进口品牌，可靠性强，耐用度高，保障机器使用寿命；  
Key components are Japanese, German or Taiwan Brand, high reliability and durability, greatly prolonged the machine lifetime
- ✓ 使用精密带反张力控制张力器，使产品排线更整齐；  
Use precision tensioner with backward tension control to achieve better wire alignment
- ✓ 采用独立式包胶装置，胶带宽窄兼容，可实现不断胶带层间隔离、收直角，且包胶平整，并能实现两边档墙胶带≤1圈；  
Adopt independent taping device, compatible for different size tape, can achieve layer isolation without tape break, straight angle and neat taping performance, Both sides margin taping ≤1 turn is achievable
- ✓ 上下料装盘同一工位时进行（空骨架、成品）；  
Bobbin loading and finished parts plating share the same station at the same time (bobbin, finished parts)
- ✓ 具有自动夹线、断线、排除废线功能。  
With wire auto holding, breaking and removing function

### Parameter

#### 技术参数

型号 Models	WZY-A7808LC/TA/TB
绕线轴距 Spindle Pitch	78mm
轴数 Spindle Numbers	8
主轴速度 Spindle Speed	8000rpm
主轴马达功率 Spindle Motor	1500W
三维马达功率 XYZ Spindle Motor	400W
适用线径 Wire Range	0.025~0.5mm (Depending on each tensioner's configuration)
最大骨架外径 Max.Bobbin OD	50mm
快速夹具接口内径 Jig Inner Diameter	10mm
电源 Power Voltage	AC 220V±10%
总功率 Power	6000W
空气压力 Air pressure	0.4~0.6mpa
机器尺寸 Machine Size	2850*1450*1850mm
机器重量 Machine Weight	~1100kgs